



- NOTES:
1. TERMINAL TO BE USED IN HOUSING 70066-**** AND 70450-****.
 2. REFER TO PRODUCT SPECIFICATION PS-70058.
 3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
 4. TERMINAL TO BE USED WITH (0.64)/.025 SQUARE PINS.
 5. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH (1.63)/.064 MAXIMUM DIAMETER INSULATION.
 6. TERMINALS SUPPLIED IN REEL FORM.
 7. CRIMP SIZE INDICATOR C=22-24 AWG

PLATING:
 .00030 MINIMUM GOLD PLATE IN SELECT AREA,
 .000075 MINIMUM TIN PLATE IN SELECT AREA,
 OVER NICKEL PLATE OVERALL.

| | | | | | | | | | |
|--|-----------------|---------------------------------------|--------|--------------------------|---|--------------------|--|------------------------|-------------------------------------|
| REEL UNWIND DIR EC NO: UCP2013-5345 DRW:RWHIPPLE 2013/06/11 CHK:D.MORGAN 2013/06/11 APPR:SMILLER 2013/07/09 REV B | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE MM/IN | | SCALE 10:1 | DESIGN UNITS INCH | THIRD ANGLE PROJECTION | |
| | ▽=0 | 4 PLACES | ± --- | ± --- | DRAWN BY MIBARRA | DATE 2005/11/16 | TITLE TERMINAL - BOX/CRIMP FOR 22-24 AWG ON A REEL | | |
| | ▽=0 | 3 PLACES | ± --- | ± .005 | CHECKED BY BBARKER | DATE 2005/11/16 | | | |
| | ▽=0 | 2 PLACES | ± 0.13 | ± .01 | APPROVED BY SMILLER | DATE 2013/07/09 | MATERIAL NO. 70058-0088 | | DOCUMENT NO. SD-70058-004 |
| | | 1 PLACE | ± 0.25 | ± --- | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | | | |
| | | 0 PLACE | ± --- | ± --- | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | |