

4

3

2

1

DESCRIPTION	MATERIAL	FINISH
SHRINK TUBING	PER MIL-I-23053/8	NONE
CLIP CONTACT RETAINING	BeCu ASTM-B-194 OR STAINLESS STEEL PER QQ-S-766	NONE
CONTACT FEMALE SOCKET	BERYLLIUM COPPER PER QQ-C-533	GOLD PLATE PER MIL-G-45204 OVER NICKEL
SPLICE ASSEMBLY HOUSING	EPIALL TYPE 1908	NONE
GROMMET	FLUROROSILICONE	COLOR - NATURAL
RESISTOR	RNC55H1503 FR 150K $\Omega$ 1/10 WATT $\pm$ 1% PER MIL-R-55182	NONE
DESCRIPTION	MATERIAL	FINISH

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	REV PER ECO-12-000064	24JAN12	PY	DE

1. THIS ASSEMBLY MEETS OR EXCEEDS THE GENERAL REQUIREMENTS OF MIL-T-81714, CLASS B

2. PIN CONTACTS, SEALING RINGS & INSERTION/EXTRACTION TOOL SHALL BE ORDERED SEPARATELY

A) PIN CONTACT: AMP P/N 2-592404-1, MILITARY P/N 39029/1-101  
 B) SEALING PLUGS: AMP P/N 592104-1, MILITARY P/N MS27488-20  
 C) INSERTION/EXTRACTION TOOL: AMP P/N 592105-1, MILITARY P/N M81969/14-11

3. ENVIRONMENTS CREATED BY THE OPERATION OF INTERNAL ELECTRONIC COMPONENTS WHICH EXCEED THE MODULE RATED PERFORMANCE IS THE RESPONSIBILITY OF THE USER. THE ELECTRONIC COMPONENT SPECIFICATIONS SHOULD BE CONSULTED.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J.A.BAKER 04-09-97	<b>STE</b> TE Connectivity	
DIMENSIONS: INCHES		CHK D.MILLER 4-11-97		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MILLER 4-11-97	NAME WIRE SPLICE, SINGLE SIZE 20	
0 PLC $\pm$ - 1 PLC $\pm$ - 2 PLC $\pm$ .01 3 PLC $\pm$ .005 4 PLC $\pm$ - ANGLES $\pm$ 30'		PRODUCT SPEC -	SIZE A2	
MATERIAL SEE TABLE		FINISH SEE TABLE	CAGE CODE 00779	DRAWING NO 591900
		WEIGHT -	RESTRICTED TO -	
		CUSTOMER DRAWING	SCALE 1:1	SHEET 1 of 1
			REV A	

1471-9 (3/11)

591900

A