



FIGURE A  
 MAXIMUM OUTPUT CURRENT OF ANY DUAL INPUT VOLTAGE OR VOLTAGE DOUBLER UNIT OPERATED AT LOWER INPUT VOLTAGE.

# MAXIMUM OUTPUT CURRENT IN OUTPUT VOLTAGE RANGE FROM 0 TO 25% ABOVE LINE VOLTAGE. AT HIGHER OUTPUT VOLTAGES, OUTPUT CURRENT MUST BE REDUCED ACCORDING TO RATING CURVE, FIGURE A.

‡ MAXIMUM KVA AT MAXIMUM OUTPUT AND CORRESPONDING DE-RATED CURRENT. MAXIMUM KVA AT LOWER OUTPUT VOLTAGES MAY BE CALCULATED FROM RATING CURVE, FIGURE A.

SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR INCREASE VOLTAGE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END	
	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA		INPUT	OUTPUT
THREE PHASE OPEN DELTA	240	50/60	0-240	35	14.5	CW	4-1-4	3-1-3
			0-280	35	16.9	CW	2-1-2	3-1-3
	120	50/60	0-280	35-15# V.D.	7.3 ‡	CW	5-1-5	3-1-3

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS: DECIMALS: .005 HOLES: .0015 ANGLES: 1/2° DRAFT: 1-1/2° DIMENSIONS APPLY UNLESS NOTED	TITLE: SPEC. CONTROL DRAWING VARIABLE TRANSFORMER TYPE: 6020-2D DRAWN BY: TIM RAU DATE: 10/28/97 CHECKER: [ ] ENGINEER: [ ] FIRST USED ON: [ ] VENDOR APPROVAL: [ ] SCALE: .5=1 SHEET 1 OF 1	THE INFORMATION AND DESIGN DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF STACO ENERGY PRODUCTS CO., WHICH RESERVES ALL PATENT, PROPRIETARY, DESIGN, MANUFACTURING, REPRODUCTION AND SALE RIGHTS THEREIN, AND TO ANY OTHERS DISCLOSED THEREIN, EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE FOREGOING DOES NOT APPLY TO VENDOR PROPRIETARY PARTS.	STACO ENERGY PRODUCTS CO. A DIVISION OF AMERICA GROUP DAYTON, OHIO U.S.A.
---	--	--	---