

Panel mounting frames - VS-V1-F-LC-MNNA-PG9-C-S-B1 - 1420223

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



LC mounting frame, IP67, for bayonet interlocking, metal, with coupling for single mode, for round mounting cutout, with seal, without mounting screws



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	80.0 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Insertion/withdrawal cycles	500
Connection method	LC

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP67

Material data

Housing material	Zinc die-cast
Seal material	NBR

Electrical characteristics

Number of positions	2
---------------------	---

Panel mounting frames - VS-V1-F-LC-MNNA-PG9-C-S-B1 - 1420223

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27261207
eCl@ss 7.0	27440210
eCl@ss 8.0	27440210

ETIM

ETIM 2.0	EC000376
ETIM 3.0	EC000376
ETIM 4.0	EC001129
ETIM 5.0	EC002310

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Drawings

Dimensioned drawing

