



RECOMMENDED LAYOUT FOR .062 THICK P.C. BOARD

REVISIONS					
P	ZONE	LTR	DESCRIPTION	DATE	APPROVED
✓		0	RELEASES NEW DRAWING 6-TT183-17	3/21/83	Dag/D.H.
✓		A	REVISED PER ECN M-7383	9-9-83	SDW
✓		B	REVISED PER ECN AG 214	1-27-84	MC
✓		B1	RESTORATION	8-24-85	K/S/NJ
✓		C	REVISE PER CM-1511	2-10-87	PKC
✓		D	OBSOLETE -1 PER CM-1376	7-12-88	PH
✓		E	REACT -1 PER PR CM 92-36	4-15-92	NJG
✓		F	REV PER ECN 0730-3928-92	1-8-93	NJG
✓		G	REV PER EC 0730-0111-95	8-29-95	JH

No. PER ASSY	DESCRIPTION	MATERIAL & FINISH	ITEM No.	PART NO
9	SOCKET	PH BRZ, PRE-TIN	2	6434-25-1
1	HOUSING	NYLON, 94V-Z, NATURAL	1	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ON: DECIMALS ±.015 ANGLES ±	CONTRACT NO		AMP INCORPORATED Harrisburg, Pa.	
	DR D.A. SALTZER 3-21-83		NAME	
MATERIAL	CHK S. Hilde 4/8/83	HEADER ASSEMBLY, SOCKET, POLARIZED		
SEE TABLE	APPD [Signature] 4/8/83	UNIVERSAL MATE-N-LOK™, 9 CIRCUIT		
FINISH	DSGN APPD	SIZE 15	FSCM NO 00779	DRAWING NO 643425
SEE TABLE	OTHER APPD	SCALE 2:1		SHEET

- 1. PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
- 2. CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAVITIES, BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.