

1

2

3

4

5

6

7

A

B

Panel Thickness  
Screw L=5.0 For Panel Thickness Under 1.2mm  
Screw L=6.0 For Panel Thickness Between 1.2-2.0mm

C

Recommended Panel Cut-Out

D

With Liquid Glue

E

NOTES:

MATERIAL

1. Insulator Material: Black, NYLON+G/F
2. Contact Material : Copper Alloy
3. Plating : Gold Plating
4. Waterproof Rate: IP67
5. Do Mating Test After Glued
6. LOGO

F

15 Pin Male Connector  
PCB Pin Layout  
Scale 2:1

G

RoHS compliant

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	24.12.2008	JACK
X.X	±0.25					Approved	24.12.2008	Hellwig
X.XX	±0.10							
X.XXX	±0.05							
DIM	TOL							
ANGLE	±1°							
X.X°	±X°	①	Drawn	24.12.2008	JACK			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No.  
**A-HDS 15 PP-WP**

Drawing-No.  
**ASS 3277 CO** rev01

Replace Sheet

H

1

2

3

4

5

6

7

A

B

C

D

E

F

G

H