

Product Overview

MM3Z2V7: 300 mW 2.7 V \pm 5% Zener Diode Voltage Regulator

For complete documentation, see the data sheet.

This Zener Diode Voltage Regulator is packaged in a SOD323 surface mount package, which has a power dissipation of 300 milliwatts. It is designed to provide voltage regulation protection and is especially attractive in situations where space is at a premium. It is well suited for applications such as cellular phones, hand held portables and high density PC boards.

Features

- Standard Zener Breakdown Voltage Range - 2.4 V to 75 V
- Steady State Power Rating of 300 mW
- Small Body Outline Dimensions: 0.067" X 0.049" (1.7 mm X 1.25 mm)
- Low Body Height: 0.035" (0.9 mm)
Mechanical Characteristics
- Package Weight: 4.507 mg/unit
- ESD Rating of Class 3 (>16 KV) per Human Body Model

Mechanical Characteristics:

- CASE: Void-free, transfer-molded plastic
- FINISH: All external surfaces are corrosion resistant
- MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds
- LEADS: Plated with Pb/Sn or Sb only (Pb-Free)

For more features, see the data sheet

Applications

- Zener voltage regulation

Part Electrical Specifications					
Product	Compliance	Status	V _Z Typ (V)	P Max (W)	Package Type
MM3Z2V7T1G	Pb-free	Active	2.7	0.3	SOD-323
	Halide free				
SZMM3Z2V7T1G	AEC Qualified	Active	2.7	0.3	SOD-323
	PPAP Capable				
	Pb-free				
	Halide free				
SZMM3Z2V7T3G	AEC Qualified	Active	2.7	0.3	SOD-323
	PPAP Capable				
	Pb-free				
	Halide free				

For more information please contact your local sales support at www.onsemi.com.

Created on: 8/20/2018