



FILTER	CAPACITANCE	PART NO.	
		M3	4-40 UNC
TYPE 1	180pF±20%	24-3811750X	24-3811630X
TYPE 3	370pF±20%	24-3811790X	24-3811670X
TYPE 4	830pF±20%	24-3811830X	24-3811710X



NOTES:

1. RoHS COMPLIANT
2. METAL SHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATORS: PBT GF UL 94 V-0, BLACK
4. CONTACTS: COPPER ALLOY
 PLATING: § USE A FOR QUALITY CLASS 3
 § USE B FOR QUALITY CLASS 2
 § USE C FOR QUALITY CLASS 1
5. THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. ADAPTER SCREW: COPPER ALLOY; NICKEL PLATED
7. CAPACITANCE: SEE TABLE
8. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
9. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
10. CONNECTOR IS PART MARKED: [PART-NO.] CONEC [ABC]

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
1	Origin		

tolerance	2:1 (5:1)	scale:	SEE NOTES
material:		material:	
title:	HD FILTER ADAPTER 62 polig		
dwg no:	24K11Q0A	CAD/ REL.13	DIN-A
product no:	SEE TABLE		
sh: 1/1	3		

