

Ratings

Temperature: 0 ~ 70 °C
Voltage: 150 V

Conductor

Gauge: 32 AWG, 0.039 mm²
Material: tinned copper strands
Strand size: $\varnothing 0.05 \times 19$ mm
Resistance at 20 °C: 590 Ω /km

Insulator

Material: HDPE
Color: black, white, yellow, red
Outer diameter: $\varnothing 0.55 \pm 0.05$ mm
Nominal thickness: 0.15 mm
Resistance at 20 °C: 1000 M Ω /km

Shield

Type: spiral
Material: tinned copper strands
Strand size: $\varnothing 0.08$ mm
Coverage: 90 % minimum

Outer jacket



Material: TPU, 70 °C
Color: cool gray 1C
Nominal thickness: 0.50 mm
Diameter: $\varnothing 2.5 \pm 0.15$ mm

Filler

Material: kevlar

Tests

Tensile strength: 25.5 kgf
Dielectric test: 1500 V dc for 1 minute without breakdown
Bend test at 200 g, $\pm 90^\circ$, 30 cycles /min: 10,000 cycle minimum



REVISION	DATE	DESCRIPTION
A	4/24/2015	Initial release
A1	1/13/2016	Updated notes, corrected tolerances

PREPARED:	NOTES RoHS and REACH compliant Jacket meets ISO 10993 Biological Compatibility Phthalate and halogen free Function test: no open, no short, no intermittent
VERIFIED:	
DIMENSIONS ARE IN MILLIMETERS	
TOLERANCES: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	
DESCRIPTION: Wire, 4C TS, 32 AWG, 150V, 70C, 2.5 mm, spiral shield, TPU, white	

TENSILITY

20802 Sockeye Place #130
Bend, OR 97701 USA
tel 541.323.3228 fax 541.323.4202
800 877.670.7118 www.tensility.com

SIZE	PART NUMBER
A	30-00446

SCALE: 20:1

SHEET 1 OF 1