

Slave protocol chip - IBS SUPI 4 QFN - 2746744

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Slave protocol chip, for INTERBUS



Key Commercial Data

| | |
|------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 250 pc |
| Custom tariff number | 85423290 |
| Country of origin | Japan |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 8 mm |
| Height | 0.9 mm |
| Depth | 8 mm |
| Length | 8 mm |

Ambient conditions

| | |
|---|--|
| Ambient temperature (storage/transport) | -65 °C ... 150 °C (at max. 60 %) |
| Ambient temperature (operation) | -40 °C ... 85 °C (at max. 75% humidity during operation) |

Module

| | |
|-----------------------------|--|
| IC power supply voltage | 3.3 V DC \pm 10 % (DC) |
| Typical current consumption | 20 mA |
| Connection method | Remote bus, local bus or installation remote bus |
| Interface | INTERBUS |
| Internal data length | 64 bytes IN/64 bytes OUT |
| User interface | MFP interface, digital I/O (16 IN/16 OUT, 32 IN, 32 OUT), parallel and serial port for microprocessors |

General

| | |
|------|----------------------------|
| Type | QFN 52 (with copper block) |
|------|----------------------------|

Slave protocol chip - IBS SUPI 4 QFN - 2746744

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250201 |
| eCl@ss 4.1 | 27250201 |
| eCl@ss 5.0 | 27250203 |
| eCl@ss 5.1 | 27249201 |
| eCl@ss 6.0 | 27242605 |
| eCl@ss 7.0 | 27242605 |
| eCl@ss 8.0 | 27242608 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001433 |
| ETIM 3.0 | EC001601 |
| ETIM 4.0 | EC001601 |
| ETIM 5.0 | EC001604 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 43201404 |