

ADH700 Series

700 Watt Half-Brick DC-DC Converter

Data Sheet

Total Power: 700 Watt
(50 V @ 14 A)
Input Voltage: 36 - 65 Vdc
Single Output: 50 V Nom

SPECIAL FEATURES

- 700 W continuous power
- Ultra high efficiency 95% @ 50% load
- 36 - 65 Vdc Telecom input range
- Contact cooling or heatsink mounting
- Excellent thermal performance
- Remote output sense
- Fully regulated output voltage
- No minimum load requirement
- Remote control function
- Low ripple and noise
- Fixed switching frequency
- Trim function: 50% ~118%
- High reliability
- RoHS 6 compliant
- UL94 V-0 materials
- Output overcurrent protection
- Output shortcircuit protection
- Output overvoltage protection
- Overtemperature protection
- Industry standard half-brick
- Two year warranty (consult factory for extended terms)

SAFETY

- EN60950
- CSA
- CE
- UL



Electrical Specifications

Input	
Input voltage	36 - 65 Vdc
Input surge	100 V / 100 mSec (Non-operation)
Input UVLO	Turn-on: 34 Vdc typical Turn-off: 32 Vdc typical Hysteresis: 2 Vdc typical
I/O insulation	Basic insulation
I/O isolation	2250 Vdc
Efficiency (48 Vin, 25 °C ambient)	95% @ 50% load 94.8% @ 100% load
Output	
Output voltage (Vin = 48 V)	50 V
Output current maximum	14 A
Noise & ripple	90 mV pk-pk typical
Overtemperature protection	115 °C typical
Overvoltage protection method / OVP operation	60 - 70 V window / Hiccup and auto restart
Overcurrent protection method / OCP operation	14.5 - 35 A window / Hiccup and auto restart
Control	
Enable	TTL compatible
Switching frequency	280 KHz fixed frequency

Environmental Specifications

Operating temperature	-40° C to +85 °C
Storage temperature	-55 °C to +125 °C
MTBF	2 million hours

Ordering Information

Model number	Input voltage	Output voltage set point	Output current	Efficiency
ADH700-48S50-6L	36 - 65 Vdc	50 Vdc	14 A	94.8% (100% load)
ADH700-48S50P-6L	36 - 65 Vdc	50 Vdc	14 A	94.8% (100% load)

B = Baseplate

-6 = 3.8 mm pin length

P = Positive logic control

Digital interface option



Pin Length Options

Device code suffix	L
-4	4.6 mm ± 0.5 mm
-6	3.8 mm ± 0.5 mm
-8	2.8 mm ± 0.5 mm
None	5.8 mm ± 0.5 mm

Pin Designations

Pin	Function	Function
1	Vin+	Positive input voltage
2	CNT	Remote ON/OFF control
3	Case	Case
4	Vin-	Negative input voltage
5	Vo-	Negative output sense
6	S-	Negative output sense
7	Trim	Output voltage trim
8	S+	Positive output sense
9	Vo+	Positive output voltage

Mechanical Drawing



UNIT: mm[inch]

L=3.80±0.25mm

TOLERANCE: X.Xmm±0.5mm[X.XX in.±0.02in.]

X.XXmm±0.25mm[X.XXX in.±0.01in.]

WORLDWIDE OFFICES

Americas

2900 S.Diablo Way
Tempe, AZ 85282
USA
+1 888 412 7832

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
+44 (0) 1384 842 211

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
+852 2176 3333

ARTESYN
EMBEDDED TECHNOLOGIES

www.artesyn.com

Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2017 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit www.artesyn.com/legal.

For more information: www.artesyn.com/power
For support: productsupport.ep@artesyn.com