



**Part Number:** 6200UE

Security & Sound, 2 Conductor 16 AWG, BC, Unshielded, CMP

## Product Description

Security & Commercial Audio Cable, Plenum-CMP 2-16 AWG stranded bare copper conductors with Flammarrest® insulation, Flammarrest® jacket with ripcord

## Technical Specifications

### Product Overview

Environmental Space:	Indoor - Plenum
Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
16	19x29	BC - Bare Copper	2

Conductor Count:	2
Conductor Size:	16 AWG

#### Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flammarrest®	0.009 in

#### Color Chart

Number	Color
1	Black
2	White

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flammarrest®	0.184 in	0.015 in	Yes

## Construction and Dimensions

#### Cabling

Lay Direction	Twists
Left Hand	4 twist/ft

## Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
3.8 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
36.5 pF/ft

Shielding:	Multiple or Specialty
------------	-----------------------

#### Inductance

<b>Nominal Inductance</b>
0.145 µH/ft

#### Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C ambient: 6.25 A

#### Voltage

<b>UL Voltage Rating</b>
300 V RMS

#### Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	60.8 lbs
Min Bend Radius/Minor Axis:	2.0 in

#### Standards

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
CPR Euroclass:	Eca

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	Y
---------------	---

#### Part Number

Non-Plenum Number:	5200UH
--------------------	--------

#### Variants

Item #	Color	Footnote
6200UE 0101000	Black	
6200UE 010U1000	Black	
6200UE 010U250	Black	
6200UE 010U500	Black	

6200UE D151000	Blue	
6200UE 008U1000	Gray	
6200UE 0051000	Green, Dark	
6200UE 8771000	Natural	C
6200UE 877500	Natural	
6200UE 877U1000	Natural	
6200UE 877U250	Natural	
6200UE 0031000	Orange	
6200UE 0021000	Red	
6200UE 0071000	Violet	
6200UE 009U1000	White	
6200UE 009U250	White	
6200UE 009U500	White	
6200UE 0091000	White	
6200UE 0041000	Yellow	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.