

Technical specification:

Rated voltage: IEC 61076-2-101	4pos 160 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperatur range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn, CuBe
Contact plating:	Nickel, gold plated
Contact carrier:	PA, UL 94
Sealing:	FPM
Coupling nut:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:



Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Contact assignment:

1	n.c.
2	Profibus-A green
3	n.c.
4	Profibus-B red
Shielding coupling nut	

Part no:	Description:	Length L:	Cable:
43-12479	SAL - 12B - RKW4.1 - 2 / G7	2m	TPE, UL, violet, 2xAWG24 Cable: 781-G70200
43-12480	SAL - 12B - RKW4.1 - 3 / G7	3m	
43-12481	SAL - 12B - RKW4.1 - 5 / G7	5m	
43-12482	SAL - 12B - RKW4.1 - 10 / G7	10m	
43-xxxxx	SAL - 12B - RKW4.1 - ... / G7	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 09.03.2011 VF Ä3767 Coupling nut modified, spanner flats added, data sheet modified	 dim. in mm	title: Female connector M12x1 angled, Profibus DP									
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>17.10.08</td> <td>Mankopf</td> </tr> <tr> <td>appd.</td> <td>17.10.08</td> <td>Fromm</td> </tr> </table>		date	name	drawn	17.10.08	Mankopf	appd.	17.10.08
		date		name								
	drawn	17.10.08		Mankopf								
appd.	17.10.08	Fromm										
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: 43K1A786										
		part no: see table										