



Directive 2002/95/EC  
„RoHS“  
Compliant

**NOTES:**

1. RoHS COMPLIANT
2. SUITABLE FOR WAVE SOLDERING
3. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
4. INSULATORS: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
5. CONTACTS: COPPER ALLOY  
PLATING: 8µm HARD GOLD over min. 50µm NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
6. THREADED INSERT: COPPER ALLOY; min 200µm TIN over 80µm NICKEL
7. COLLAR: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
8. CAPACITANCE: 2 x 370pF ± 20%
9. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
10. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
11. CONNECTOR IS PART MARKED: 241A29300X CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
a	Origin		

finish:	tolerance		scale: 2:1 (5:1)
		dim. in mm	material: SEE NOTES
	date	name	title: D-SUB PI FILTER MALE 25pos. SOLDER CUP with threaded insert
	drawn: 22.11.07	Sonnenberg	dwg no: Inventor
	appd.: 22.11.07	Mickenbecker	24K1A1057
	norm: DIN 41652		DIN-A3
	d-old		sh: 1
			part no: 241A29300X

**CONEC**