

SPECIFICATION CONTROL DRAWING


55PC2132

TITLE **THREE CONDUCTOR CABLE, FLAT BRAID SHIELDED, JACKETED, 600 VOLT**

Date **6-22-95**

Revision **D**

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD STRAND THICKNESS (± .0004)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC2132-26-*	26	.0015	.0060	.0080	.084	.089	.094	6.71	7.22
55PC2132-24-*	24	.0015	.0060	.0080	.095	.100	.105	8.89	9.45
55PC2132-22-*	22	.0015	.0060	.0080	.108	.113	.118	12.09	12.72
55PC2132-20-*	20	.0015	.0065	.0085	.126	.131	.136	17.21	17.95
55PC2132-18-*	18	.0015	.0065	.0085	.146	.152	.157	24.62	25.60
55PC2132-16-*	16	.0015	.0065	.0085	.161	.168	.175	30.67	31.93
55PC2132-14-*	14	.0015	.0070	.0090	.194	.200	.206	45.38	46.79
55PC2132-12-*	12	.0015	.0070	.0090	.235	.241	.248	67.69	69.54

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
 Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms)
DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz
CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour
JACKET COLOR: White preferred
JACKET ELONGATION AND TENSILE STRENGTH:
 Elongation, 50% (minimum)
 Tensile Strength, 5000 lbf/in² (minimum)
JACKET FLAWS:
 Spark Test, 1000 volts (rms), 60 Hz, 100% test
 Impulse Dielectric Test, 6.0 kV (peak), 100% test

SHIELD COVERAGE: 85% (minimum)
VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):
 1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:
 The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.
 Example: AWG 22, red, blue and yellow component white jacket: 55PC2132-22-2/6/4-9

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-881.

Raychem

Raychem Corporation
 300 Constitution Drive, Menlo Park, California 94025
 1-800-2-Raychem Fax: 1-415-361-6297