

Thermal transfer printer - THERMOFOX - 0803984

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Portable thermal transfer printer for roll material

Why buy this product

- ✓ Maintenance-free operation with proven thermal transfer printing technology
- ✓ Easy to control with the CLIP PROJECT software
- ✓ Printing of self-adhesive, non-sticky labels and shrink sleeves
- ✓ The THERMOFOX prints materials in cassette format, which contain the material to be marked and the appropriate ink ribbon.
- ✓ Intuitive user guidance thanks to a well-structured menu and direct input keys
- ✓ 8 different barcodes and over 300 symbols can be integrated.
- ✓ Alternative control via the CLIP PROJECT software



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 212586
GTIN	4055626212586

Technical data

General

Interface	USB
Weight	656.00 g

Dimensions

Length	230.00 mm
Height	69.00 mm
Width	98.00 mm

Connection data

Minimum voltage	100 V AC
Max. voltage	240 V AC

Thermal transfer printer - THERMOFOX - 0803984

Technical data

Connection data

Additional text	50 Hz ... 60 Hz
-----------------	-----------------

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 10;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals


Approvals

Approvals

EAC / KC

Ex Approvals

Approval details

EAC		RU D- DE.ME06.B.02060
-----	---	--------------------------

KC		http://eng.kcc.go.kr/user/ehpMain.do	MSIP-REM-YG3
----	---	---	--------------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>