



P1




Conductor: [26AWG(0.16/7)Bare Copper]x6C
 Insulation: [PP6331 ID:0.95±0.03]x6C
 Jacket: PVC NOUL 65P

White
 Black
 Red
 Green
 Yellow
 Blue

P1	COLOR
1	WHITE
2	BLACK
3	RED
4	GREEN
5	YELLOW
6	BLUE



A, B, C, D



E, F, G

Note:

- Material: Housing-polycarbonate, clear
- Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/S-5-OE	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-6/6/S-7-OE	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-6/6/S-10-OE	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-6/6/S-12-OE	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-6/6/S-14-OE	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-6/6/S-25-OE	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-6/6/S-50-OE	G	15,250±150(50ft)	Silver	15,250-15,260mm

Unit: mm



Scale	Free					Date	Name
TOLERANCE						Drawn	28.06.13
X.	±X					Approved	28.06.13
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name	 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us	

Title
 Modular cable - Straight/Open
 6P6C 50µ", 26AWG, Silver, 5-50 feet

ASSMANN WSW-No.
AT-S-26-6/6/S-xx-OE

Drawing-No.

Replace

Sheet
 1/1

rev00

