



Part Number: 29500F

1000V UL Flexible Motor VFD, (3) 16 AWG (65x34) TC+Grd, XLP/TPE, Foil+TC Braid Shld, TC-ER

[Request Sample](#)

Product Description

Three 16 AWG stranded (65x34) tinned copper circuit conductors plus ground wire, cross-linked polyolefin insulation, Overall Duofoil® (100% coverage) plus a tinned copper braid shield (85% coverage), TPE jacket.

Technical Specifications

Product Overview

Suitable Applications:	AC Motor drives, VFD, Variable Frequency drives
------------------------	---

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	No. of Conductors
	16	65x34	TC - Tinned Copper	3
Ground Wire	16	65x34	TC - Tinned Copper	

Conductor Count:	3
Conductor Size:	16 AWG

Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.045 in
XLP - Cross Linked Polyolefin	0.045 in

Color Chart

Number	Color
1	Black and Numbered 1
2	Black and Numbered 2
3	Black and Numbered 3
4	Green/Yellow

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	1	Aluminum/Polyester	Duofoil®	100 %	TC - Tinned Copper	16
Braid	2	TC - Tinned Copper		85 %		

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
TPE - Thermoplastic Elastomer	0.528 in	0.063 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
21 pF/ft	38 pF/ft
Shielding:	Foil + Braid(s)

Inductance

Nominal Inductance

0.23 µH/ft

Impedance

Nominal Characteristic Impedance

90 Ohm

Current

Max. Recommended Current [A]

18 Amps per conductor @ 30°C (per NEC)

Voltage

UL Voltage Rating

1000 V RMS (Flexible Motor Supply Cable)

600 V RMS (NEC Type TC)

Temperature Range

Operating Temp Range: -40C To +90C Wet/Dry

Mechanical Characteristics

Bulk Cable Weight: 128 lbs/1000ft

Max Recommended Pulling Tension: 128 lbs

Min Bend Radius (Continuous Flexing): 4 in

Min Bend Radius/Minor Axis: 2.6 in

Standards

NEC Articles: 336 - ER

NEC/(UL) Specification: N/A

CEC/C(UL) Specification: 600V Type CIC TC

Other Specification: 1000V UL Flexible Motor Supply

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-10-13

CA Prop 65 (CJ for Wire & Cable): Yes

Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: Yes

Suitability - Sunlight Resistance: Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: UL1685 UL Loading

CSA Flammability: FT4

IEEE Flammability: 1202, 383 Vertical Tray Flame Test (70,000 BTU)

UL voltage rating: 1000 V RMS (Flexible Motor Supply Cable)

Part Number

Variants

Item #	Color
29500F 0101000	Black
29500F 0106000	Black

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.