

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

- . - .

LOC

DIST

REVISIONS

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

P

LTR

DESCRIPTION

DATE

DWN

APVD

E2

REVISED PER ECR-12-013357

08JAN13

MZ

YHM

ロックタイプII
LOCK TYPE II回路番号
CIRCUIT NO.本図ロックタイプIを示す
AS SHOWN LOCK TYPE II

注

1. 適用コンタクト型番:
リセコンタクト: 177915-X (AWG#20-#16)
177914-X (AWG#26-#22)
2. かん合相手製品型番
キャップハウジング: 177907-X (パネル取付タイプ)
179464-X (宙吊りタイプ)
タブコンタクト: 177917-X (AWG#20-#16)
177916-X (AWG#26-#22)
3. 適用プレート型番: 177919-X
4. 取扱説明書: 411-5638
5. 表1参照回路番号
CIRCUIT NO.

NOTES

1. APPLICABLE CONTACT P/N
REC CONTACT: 177915-X (AWG#20-#16)
177914-X (AWG#26-#22)
2. MATIN CONN. P/N
CAP HSG: 177907-X (PANEL MOUNT)
179464-X (FREE HANGING)
TAB CONTACT: 177917-X (AWG#20-#16)
177916-X (AWG#26-#22)
3. APPLICABLE PLATE P/N: 177919-X
4. INSTRUCTION SHEET: 411-5638
5. SEE TABLE 1
6. ALL PARTS MEET RTI ELECTRICAL RATING
OF 105°C ACCORDING TO UL1977.

表1 TABLE 1

トレードマーク TRADE MARK	生産場所 MANUFACTURING LOCATION
-AMP OR AMP	日本 JAPAN
-+AMP OR AMP	中国 CHINA (PRC)
•AMP OR AMP	韓国 KOREA

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差10 ≤ ±0.2
10 < 30 ±0.25
30 < 100 ±0.3ANGLES
FINISH
仕上 ±3'MATERIAL
材料

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

25OCT2007

25OCT2007

25OCT2007

108-5410

取付適用規格

A3

00779

C=177899

NAME

CAGE CODE

DRAWING NO

RESTRICTED TO

SCALE

SHEET

REV

E2

TE Connectivity

AMP POWER DOUBLE LOCK CONN
3.96MM PITCH PLUG HOUSING
3POS (SGL ROW)

SIZE

A3

00779

CAGE CODE

00779

C=177899

DRAWING NO

C=177899

RESTRICTED TO

SCALE

4:1

SHEET

1

OF 1

REV

E2

1470-19 (3/11)