

# Fuse plug - PV-C-M/F-PRO/F-1000/25-EU - 1622158

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1000 V/25 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1000 V system voltage

## Product Description

SUNCLIX fuse connector, for 1000 V system voltage, fuse-link nominal current of 25 A, EU version

## Why buy this product

- One-piece design
- Robust, easy-to-install fuse element for outdoor use
- High-quality fuse-link
- Degree of protection: IP68 (24 h/2 m)
- 
- 1000 V (EN)



## Key Commercial Data

Packing unit	8 STK
Minimum order quantity	8 STK
GTIN	
GTIN	4055626130705

## Technical data

### Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 50 °C

### General

Rated voltage	1000 V
Fuse-link nominal current	25 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	25 A DC

# Fuse plug - PV-C-M/F-PRO/F-1000/25-EU - 1622158

## Technical data

### Material

Flammability rating according to UL 94	V0
--	----

### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



## Approvals

### Approvals

---

### Approvals

EAC

---

### Ex Approvals

---

### Approval details

EAC		B.01742
-----	--	---------

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>