



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X±0.4  
X.XX±0.25
  3. TERMINAL NUMBERS FOR REF. ONLY
  4. CONTACT RATING: 0.1A @ 30VDC
  5. TRAVEL: FULL = 2.5±0.3
  6. OPERATING FORCE: 250± 100gf
  7. ELECTRICAL LIFE: 10,000 CYCLES
  8. ▲ DENOTES CRITICAL PARAMETER
  9. CONTACT MATERIAL: SILVER
  10. CONTACT RESISTANCE: 50m OHM MAX.
  11. OPERATING TEMPERATURE: -20c TO +70c
  12. INSULATION RESISTANCE: 100M OHMS MIN.
  - ▲ 13. LED COLOR: BLUE
  14. 2002/95/EC (RoHS) COMPLIANT AND HALOGEN FREE

▲ LED SPECS	UNITS	BLUE
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	3.5-4.0
LUMINOUS INTENSITY	MCD	1,500

TITLE TL22050ABPBB	
SCALE 2:1	DATE 1/20/2010
DR rc	DWG B40103
REV	REV B

B	19554	DIM CHANGES & UPDATE	12/30/10	BGL
A	18806	New-Release	1/20/10	rc
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED